


# Evaluations on Matching Quality for 19 Different Descriptors and BRISK Keypoints over Various Inlier Ratios

Josef Maier<sup>1</sup>, Martin Humenberger<sup>1</sup>, Oliver Zendel<sup>1</sup>, and Markus Vincze<sup>2</sup>


<sup>1</sup> AIT Austrian Institute of Technology  
{josef.maier.fl, martin.humenberger,  
oliver.zendel}@ait.ac.at

<sup>2</sup> Vienna University of Technology  
vincze@acin.tuwien.ac.at


**Abstract.** In this document, we present additional results on the mean accuracy, precision, recall, and fall-out over various inlier ratios. The evaluations are performed on numerous datasets for different descriptors using BRISK [1] keypoints.




**Fig. 1.** Varying inlier ratio compared to mean (a) accuracy, (b) precision, (c) recall, and (d) fall-out using BRISK keypoints for the entire **KITTI disparity dataset** from Menze and Geiger [2]. For comparison, the following descriptors were used: BOLD [3], BRISK [1], DAISY [4], FREAK [5], LATCH [6], ORB [7], RIFF [8], SIFT [9], BGM-Bilinear (BGM-BI) [10], BGM-Hard (BGM-H) [10], BGM [10], LBGM [10], Bin-Boost [11, 12] with a descriptor size of 64 bits (BB64), 128 bits (BB128), and 256 bits (BB256), in addition to the VGG descriptor [13] with a descriptor size of 48 bits (VGG48), 64 bits (VGG64), 80 bits (VGG80), and 120 bits (VGG120). On the results of all algorithms, a ratio test was performed.




**Fig. 2.** Varying inlier ratio compared to mean (a) accuracy, (b) precision, (c) recall, and (d) fall-out using BRISK keypoints for the entire **KITTI flow dataset** from Menze and Geiger [2]. For comparison, the following descriptors were used: BOLD [3], BRISK [1], DAISY [4], FREAK [5], LATCH [6], ORB [7], RIFF [8], SIFT [9], BGM-Bilinear (BGM-BI) [10], BGM-Hard (BGM-H) [10], BGM [10], LBGM [10], BinBoost [11, 12] with a descriptor size of 64 bits (BB64), 128 bits (BB128), and 256 bits (BB256), in addition to the VGG descriptor [13] with a descriptor size of 48 bits (VGG48), 64 bits (VGG64), 80 bits (VGG80), and 120 bits (VGG120). On the results of all algorithms, a ratio test was performed.




**Fig. 3.** Varying inlier ratio compared to mean (a) accuracy, (b) precision, (c) recall, and (d) fall-out using BRISK keypoints for the entire **“graffiti”** dataset from Mikolajczyk *et al.* [14, 15]. For comparison, the following descriptors were used: BOLD [3], BRISK [1], DAISY [4], FREAK [5], LATCH [6], ORB [7], RIFF [8], SIFT [9], BGM-Bilinear (BGM-BI) [10], BGM-Hard (BGM-H) [10], BGM [10], LBGM [10], BinBoost [11, 12] with a descriptor size of 64 bits (BB64), 128 bits (BB128), and 256 bits (BB256), in addition to the VGG descriptor [13] with a descriptor size of 48 bits (VGG48), 64 bits (VGG64), 80 bits (VGG80), and 120 bits (VGG120). On the results of all algorithms, a ratio test was performed.




**Fig. 4.** Varying inlier ratio compared to mean (a) accuracy, (b) precision, (c) recall, and (d) fall-out using BRISK keypoints for the entire “bark” dataset from Mikolajczyk *et al.* [14, 15]. For comparison, the following descriptors were used: BOLD [3], BRISK [1], DAISY [4], FREAK [5], LATCH [6], ORB [7], RIFF [8], SIFT [9], BGM-Bilinear (BGM-BI) [10], BGM-Hard (BGM-H) [10], BGM [10], LBGM [10], BinBoost [11, 12] with a descriptor size of 64 bits (BB64), 128 bits (BB128), and 256 bits (BB256), in addition to the VGG descriptor [13] with a descriptor size of 48 bits (VGG48), 64 bits (VGG64), 80 bits (VGG80), and 120 bits (VGG120). On the results of all algorithms, a ratio test was performed.



**Fig. 5.** Varying inlier ratio compared to mean (a) accuracy, (b) precision, (c) recall, and (d) fall-out using BRISK keypoints for the entire “boat” dataset from Mikolajczyk *et al.* [14, 15]. For comparison, the following descriptors were used: BOLD [3], BRISK [1], DAISY [4], FREAK [5], LATCH [6], ORB [7], RIFF [8], SIFT [9], BGM-Bilinear (BGM-BI) [10], BGM-Hard (BGM-H) [10], BGM [10], LBGM [10], BinBoost [11, 12] with a descriptor size of 64 bits (BB64), 128 bits (BB128), and 256 bits (BB256), in addition to the VGG descriptor [13] with a descriptor size of 48 bits (VGG48), 64 bits (VGG64), 80 bits (VGG80), and 120 bits (VGG120). On the results of all algorithms, a ratio test was performed.




**Fig. 6.** Varying inlier ratio compared to mean (a) accuracy, (b) precision, (c) recall, and (d) fall-out using BRISK keypoints for the entire “**wall**” dataset from Mikolajczyk *et al.* [14, 15]. For comparison, the following descriptors were used: BOLD [3], BRISK [1], DAISY [4], FREAK [5], LATCH [6], ORB [7], RIFF [8], SIFT [9], BGM-Bilinear (BGM-BI) [10], BGM-Hard (BGM-H) [10], BGM [10], LBGM [10], BinBoost [11, 12] with a descriptor size of 64 bits (BB64), 128 bits (BB128), and 256 bits (BB256), in addition to the VGG descriptor [13] with a descriptor size of 48 bits (VGG48), 64 bits (VGG64), 80 bits (VGG80), and 120 bits (VGG120). On the results of all algorithms, a ratio test was performed.




**Fig. 7.** Varying inlier ratio compared to mean (a) accuracy, (b) precision, (c) recall, and (d) fall-out using BRISK keypoints for the entire “bikes” dataset from Mikolajczyk *et al.* [14, 15]. For comparison, the following descriptors were used: BOLD [3], BRISK [1], DAISY [4], FREAK [5], LATCH [6], ORB [7], RIFF [8], SIFT [9], BGM-Bilinear (BGM-BI) [10], BGM-Hard (BGM-H) [10], BGM [10], LBGM [10], BinBoost [11, 12] with a descriptor size of 64 bits (BB64), 128 bits (BB128), and 256 bits (BB256), in addition to the VGG descriptor [13] with a descriptor size of 48 bits (VGG48), 64 bits (VGG64), 80 bits (VGG80), and 120 bits (VGG120). On the results of all algorithms, a ratio test was performed.





**Fig. 8.** Varying inlier ratio compared to mean (a) accuracy, (b) precision, (c) recall, and (d) fall-out using BRISK keypoints for the entire “**JPEG**” dataset from Mikolajczyk *et al.* [14, 15]. For comparison, the following descriptors were used: BOLD [3], BRISK [1], DAISY [4], FREAK [5], LATCH [6], ORB [7], RIFF [8], SIFT [9], BGM-Bilinear (BGM-BI) [10], BGM-Hard (BGM-H) [10], BGM [10], LBGM [10], BinBoost [11, 12] with a descriptor size of 64 bits (BB64), 128 bits (BB128), and 256 bits (BB256), in addition to the VGG descriptor [13] with a descriptor size of 48 bits (VGG48), 64 bits (VGG64), 80 bits (VGG80), and 120 bits (VGG120). On the results of all algorithms, a ratio test was performed.



**Fig. 9.** Varying inlier ratio compared to mean (a) accuracy, (b) precision, (c) recall, and (d) fall-out using BRISK keypoints for the entire “light” dataset from Mikolajczyk *et al.* [14, 15]. For comparison, the following descriptors were used: BOLD [3], BRISK [1], DAISY [4], FREAK [5], LATCH [6], ORB [7], RIFF [8], SIFT [9], BGM-Bilinear (BGM-BI) [10], BGM-Hard (BGM-H) [10], BGM [10], LBGM [10], BinBoost [11, 12] with a descriptor size of 64 bits (BB64), 128 bits (BB128), and 256 bits (BB256), in addition to the VGG descriptor [13] with a descriptor size of 48 bits (VGG48), 64 bits (VGG64), 80 bits (VGG80), and 120 bits (VGG120). On the results of all algorithms, a ratio test was performed.

## References

1. Leutenegger, S., Chli, M., Siegwart, R.Y.: Brisk: Binary robust invariant scalable keypoints. In: International Conference on Computer Vision. (November 2011) 2548–2555
2. Menze, M., Geiger, A.: Object scene flow for autonomous vehicles. In: IEEE Conference on Computer Vision and Pattern Recognition (CVPR). (2015) 3061–3070
3. Balntas, V., Tang, L., Mikolajczyk, K.: Bold - binary online learned descriptor for efficient image matching. In: IEEE Conference on Computer Vision and Pattern Recognition (CVPR). (June 2015) 2367–2375
4. Tola, E., Lepetit, V., Fua, P.: Daisy: An efficient dense descriptor applied to wide-baseline stereo. *IEEE Transactions on Pattern Analysis and Machine Intelligence* **32**(5) (May 2010) 815–830
5. Alahi, A., Ortiz, R., Vandergheynst, P.: FREAK: Fast Retina Keypoint. In: IEEE Conference on Computer Vision and Pattern Recognition (CVPR). (2012) 510–517
6. Levi, G., Hassner, T.: LATCH: learned arrangements of three patch codes. *CoRR* **abs/1501.03719** (2015)
7. Rublee, E., Rabaud, V., Konolige, K., Bradski, G.: Orb: An efficient alternative to sift or surf. In: Proceedings of the International Conference on Computer Vision. ICCV '11, Washington, DC, USA, IEEE Computer Society (2011) 2564–2571
8. Wu, S., Lew, M.S.: Riff: Retina-inspired invariant fast feature descriptor. In: Proceedings of the 22Nd ACM International Conference on Multimedia. MM '14, New York, NY, USA, ACM (2014) 1129–1132
9. Lowe, D.G.: Distinctive Image Features from Scale-Invariant Keypoints. *International Journal of Computer Vision* **60**(2) (2004) 91–110
10. Trzcinski, T., Christoudias, M., Lepetit, V., Fua, P.: Learning image descriptors with the boosting-trick. In: Proceedings of the 25th International Conference on Neural Information Processing Systems. NIPS'12, USA, Curran Associates Inc. (2012) 269–277
11. Trzcinski, T., Christoudias, M., Fua, P., Lepetit, V.: Boosting binary keypoint descriptors. In: IEEE Conference on Computer Vision and Pattern Recognition (CVPR), Washington, DC, USA, IEEE Computer Society (2013) 2874–2881
12. Trzcinski, T., Christoudias, M., Lepetit, V.: Learning image descriptors with boosting. *IEEE Transactions on Pattern Analysis and Machine Intelligence* **37**(3) (March 2015) 597–610
13. Simonyan, K., Vedaldi, A., Zisserman, A.: Learning local feature descriptors using convex optimisation. *IEEE Transactions on Pattern Analysis and Machine Intelligence* **36**(8) (August 2014) 1573–1585
14. Mikolajczyk, K., Schmid, C.: A performance evaluation of local descriptors. *IEEE Transactions on Pattern Analysis and Machine Intelligence* **27**(10) (2005) 1615–1630
15. Mikolajczyk, K., Tuytelaars, T., Schmid, C., Zisserman, A., Matas, J., Schaffalitzky, F., Kadir, T., Gool, L.V.: A Comparison of Affine Region Detectors. *International Journal of Computer Vision* **65**(1-2) (2005) 43–72